

Component - Plastics

E178485

**BAYER MATERIAL SCIENCE LTD**

77TH FL, THE CENTER, 99 QUEEN'S RD, CENTRAL HK

**2400+(f1), 2407+(f1), 2456+, 2458+****Polycarbonate (PC), "Makrolon", furnished as pellets**

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	0.75	V-2	-	-	125	115	125
	1.5-2.6	V-2	3	0	125	115	125
	2.7	HB	3	0	125	115	125
	3.0	HB	2	0	125	115	125
	6.0	HB	0	0	125	115	125

Comparative Tracking Index (CTI): **2**Dimensional Stability (%): **0.0**High-Voltage Arc Tracking Rate (HVTR): **0**High Volt, Low Current Arc Resis (D495): **5**Dielectric Strength (kV/mm): **25**Volume Resistivity (10xohm-cm): **-****(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.****+ - Material designations may be followed by suffix numbers and/or letters denoting color.**

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

Report Date: 1998-05-20

Last Revised: 2007-06-21

Underwriters Laboratories Inc®

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness Tested (mm)	Value
IEC Flammability	IEC 60695-11-10	Class (color)	0.75	V-2 (ALL)
			1.5-2.6	V-2 (ALL)
			2.7	HB75 (ALL)
			3.0	HB40 (ALL)
			6.0	HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m2	-	-
ISO Izod Impact	ISO 180	kJ/m2	-	-
ISO Charpy Impact	ISO 179-2	kJ/m2	-	-

Underwriters Laboratories Inc®